



POINT-TO-POINT

TrangoLINK-45™

45 Mbps Wireless Ethernet Bridge
Multi-band: 5.2, 5.3, 5.4 or 5.8 GHz*

POINT-TO-POINT HIGH-CAPACITY BACKHAUL NETWORKS

The TrangoLINK-45™ is a 5 GHz (5180 - 5850 MHz)*, point-to-point OFDM Wireless Ethernet Bridge capable of sustained throughput of 45 Mbps with outstanding features including Dynamic Frequency Selection (DFS), Automatic Transmit Power Control (ATPC) and Adaptable Rate Modulation. TrangoLINK-45™ provides exceptional performance and value as a high-capacity solution for ISP backhaul, Enterprise and municipal connectivity, IP video surveillance systems, and “last mile” dedicated connectivity solutions (Internet, T1, leased-lines).

Management Features

- » Remote & local management via Telnet, SNMP and HTTP
- » Asymmetrical bandwidth control, and remote temperature and input voltage measurements
- » Built-in LED alignment tool, universal mounting bracket to minimize deployment costs

Interference Mitigation

- » Forwarding Error Correction (FEC)
- » Automatic Repeat reQuest (ARQ)
- » Automatic RF Transmit Power Control (ATPC)
- » Site survey tools

Compact/Rugged Designed for Outdoor Deployment

- » Fully weatherized outdoor units
- » Encased in a heavy-duty aluminum housing
- » Rugged conduit adapter, while offering a small footprint
- » Powered using Power-over-Ethernet (PoE) ensuring ease of installation and quick deployment

Highlights

- Up to 45 Mbps usable data throughput
- Multi-band versatility: 5.2, 5.3, 5.4, 5.8 GHz *
- Up to 45-mile range
- Orthogonal Frequency Division Multiplexing

Performance & Flexibility

- » License-exempt 5.8 GHz ISM band, the lower 5.3 GHz U-NII band, and the upper 5.4 GHz U-NII band *
- » OFDM radio with a contention-free point-to-point protocol
- » User-selectable data rates of 6, 12, 18, 24, 36, 48 and 54 Mbps
- » Dynamic Frequency Selection in 5.3 / 5.4 GHz
- » Packet aggregation allows superior FTP performance over long transmission ranges

Antenna Versatility

- » Horizontal or vertical software-selectable antenna polarity
- » EXT model features 2 connectors for dish antenna
- » Integrated antenna models feature built-in dual-polarity panel antennas

Channel Flexibility & Frequency Agility

- » 24 possible non-overlapping channels across the U-NII and ISM bands *
- » Up to 24 channels combined with dual-polarized antennas allows for exceptional frequency agility *

Security and Authentication

- » MAC level address authentication
- » 128-bit proprietary encryption, over-the-air data scrambling
- » Two-level password control via SSL for secure operation

Compatibility / Range Chart

MODEL	PART NUMBER	MODEL TYPE	ANTENNA	RANGE / FADE MARGIN †	
				5 MBPS	45 MBPS
TrangoLINK-45™	P5055M-19-IC	Radio w/ integrated 19 dBi Antenna	Internal, 19 dBi	12 miles / 16 dB	2 miles / 10 dB
TrangoLINK-45™	P5055M-23-IC	Radio w/ integrated 23 dBi Antenna	Internal, 23 dBi	20 miles / 21 dB	6 miles / 12 dB
TrangoLINK-45™	P5055M-EXT-IC	Connectorized radio	External, 34 dBi †	45 miles / 36 dB	20 miles / 22 dB

‡ At 5725-5850 of the ISM band.

† Based on third-party antenna not supplied by Trango.

Specifications

RADIO PARAMETERS				
Frequencies of Operation	5180 MHz - 5350 MHz (U-NII), 5470 MHz - 5725 MHz (U-NII), and 5725 MHz - 5850 MHz (ISM)			
Channels *	24 possible non-overlapping channels (US model: 21 / Europe model: 19 / OEM model: 24) *			
Channel Spacing	20 MHz			
RF Power Output (P5055M-19-IC)	Model	U-NII (5250 MHz - 5350 MHz)	U-NII (5470 MHz - 5725 MHz)	ISM (5725 MHz - 5850 MHz)
	IC model	+10 dBm max	+10 dBm max	+21 dBm @ 6 Mbps; +17 dBm @ 54 Mbps
	Europe model	+4 dBm max	+11 dBm max	N/A
	OEM model	+18 @ 6 Mbps, 14 @ 54 Mbps	+18 @ 6 Mbps, 14 @ 54 Mbps	+21 @ 6 Mbps, 17 @ 54 Mbps
Antenna Polarizations	Horizontal/Vertical (software switchable)			
Modulation Format	OFDM (BPSK, QPSK, 16 QAM, 64 QAM)			
Modulation Speeds	6, 12, 18, 24, 36, 48 and 54			
Regulatory Compliance *	FCC 15.109, FCC 15.203, FCC 15.205, FCC 15.207, FCC 15.209, FCC 15.247, FCC 15.407, Class B Digital device verification, IC-RSS210 (Canada); EN-301-489-17 (EMC), EN-301-893 (radio compliance), EN 60950 (safety), EN 50385 (RF-exposure)			
Receiver Sensitivity (10-5 BER)	-90 dBm (6 Mbps mode) to -73 dBm (54 Mbps mode) typical			
DATA AND OPERATIONAL PARAMETERS				
User Data Throughput	5 Mbps (6 Mbps mode) to 45 Mbps (54 Mbps mode)			
Upstream/Downstream Throughput	Dynamic, automatically adjust to suit demand			
Bandwidth Control	Asymmetrical MIR bandwidth control			
Latency	< 5 ms			
Interference Handling	Forward Error Correction (FEC) & Automatic Retransmit Request (ARQ)			
Security	Proprietary MAC address authentication; over the air data scrambling; two level password control.			
Encryption	128-bit STEP (Secure Trango Encryption Protocol)			
Configuration & Management	Telnet, SNMP, HTTP; TFTP server daemon for firmware upgrades; Built-in Link Performance tests; Remote temperature and input voltage measurement.			
DFS / ATPC	DFS/TPC support for operation in U-NII band			
PHYSICAL INTERFACES				
Ethernet (via shielded RJ45)	10/100 BaseT, auto-sense, auto-negotiate			
Reset Switch	Reset radio to factory default: IP address, subnet mask, gateway and password			
LED Indicators	7 LEDs including 4 RSSI			
ANTENNA OPTIONS				
TrangoLINK-45™ P5055M-19-US (integrated antenna)	Gain: 19 dBi, E-plane Beamwidth: 18°, H-Plane Beamwidth: 18° Dimensions: 8.5" x 7.75" x 1.25" (216 mm x 197 mm x 32 mm); Weight: 2 lbs (91Kg)			
TrangoLINK-45™ P5055M-23-US (integrated antenna)	Gain: 23 dBi, E-plane Beamwidth: 9°, H-Plane Beamwidth: 9° Dimensions: 14.6" x 14.6" x 1.58" (371 mm x 371 mm x 40 mm); Weight: 5.5 lbs (2.51Kg)			
TrangoLINK-45™ P5055M-EXT-US (optional external antenna †)	28 to 34 dBi dual-polarized dish antennas, 2-4 ft. diameter †			
POWER PARAMETERS				
Power Method	Power-over-Ethernet (PoE) via DC voltage injected at PoE J-box			
Voltage Input Limits into Radio	10.5 VDC to 24 VDC max			
Standard power supply	90 - 260 VAC			
PoE Cat-5 max cable Length	300 feet on 24AWG STP Cat-5 cable			
Power	10 watts nominal			
PHYSICAL AND ENVIRONMENTAL				
External Antenna Connector	SMA reverse polarity (-EXT Models only)			
Mounting Provision	Mounts to wall or pole (1" diameter or greater)			
Reset Button	Reset password and IP configuration			
Radio enclosure	All-weather, powder coated, heavy duty aluminum construction with conduit adapter			
Radio dimensions	P5055M-EXT-US stand-alone radio: 7" x 7"; P5055M-19-US and P5055M-23-US models: see Antenna Options			
Radio Weight	P5055M-EXT-US stand-alone radio: 3 lbs; P5055M-19-US and P5055M-23-US models: see Antenna Options			
Temperature Range	-40° to 60° C (-40° to 140° F)			
User Interface	RJ45 (shielded)			

All specifications are typical and subject to change without notice.

* Legal regulations for specific frequencies vary from region to region—users are responsible for complying with their region's regulations.

WWW.TRANGOBROADBAND.COM

Trango Broadband Wireless

A division of Trango Systems, Inc.
15070 Avenue of Science, Suite 200
San Diego, CA 92128

Tel.: +1 (858) 653-3900
Fax: +1 (858) 621-2725
Email: sales@trangobroadband.com

