



Removable Stainless Spring Fibreglass Bull Bar OMNI Antenna 3G/4G

NG7OMNI-6R-F NG9OMNI-6R-F NG79OMNI-6R-F



NG7OMNI-6R-F NG9OMNI-6R-F NG79OMNI-6R-F

These rugged 6R series of outdoor Omni antenna have a white removable fibreglass radiator and stainless steel spring. Available models include 7dBi, 9dBi or combo kit comprising 7 and 9dBi radiator. Designed for use on vehicles, the wideband frequency range of 690 to 2700MHz provides versatility for connections to 3G/4G/LTE services across Australia. Comes with a 5 meter LMR195 grade cable terminated with FME Female connector.



Recommendations/Installation

Ideal for mounting on vehicle bull bars or bonnet/boot using optional stainless steel mounting brackets. Good for hilly and flat terrain with poor to marginal service areas 1 bar. Wrench used to fasten bottom nut, screwdriver and other tools may also be needed depending on mounting option. Cable must be run from the antenna to interior of the vehicle. Skills required.

Specifications:	NG7OMNI-6R-F	NG9OMNI-6R-F	NG79OMNI-6R-F
Freq. Range MHz	690-960/1710-2170/2300-2700		
Gain dBi	7/3/2.5	9/4/3	7/3/2.5 or 9/4/3
VSWR	<2.6:1		
Impedance	50 ohm		
Polarization	Vertical		
Radiation	OMNI		
Material	Fibreglass Radiator, Stainless Steel Spring		
Colour	White		
Weight Grams	650	750	900
Max. Power Watts	50		
Connector	FME Female optional SMA Male		
Cable	5m Low Loss LMR195 grade		
Mounting Method	Nut fastened 15.7mm diameter Threaded Stud		
Dimensions mm	840	1370	840/1370
Temp. Rating degrees C	-20 to +60		

Email: sales@comnet.com.au
 Website: www.comnet.com.au
 Telephone: +61 2 9899 5700

Comnet Solutions
 19/9 Hoyle Avenue
 Castle Hill NSW 2154
 Australia