

## Ceiling Dome Antenna 3G/4G/5G

### CFG-CA22



These Omni ceiling dome antennas are designed for high gain 3G/4G/5G coverage. The antenna has a wide frequency band (698-3800MHz), Low PIM and Low VSWR. Designed for in building DAS applications. Comes with a RG402 pigtail cable terminated with N Female connector.

#### Recommendations/Installation

These antennas are designed for ceiling mount applications.

#### Specifications:

Freq. Range <b>MHz</b>	690-960	1700-3800
Gain <b>dBi</b>	3	5
Beamwidth <b>degrees</b>	H: 360 V: 85	H: 360 V: 45
VSWR	<1.8	
PIM <b>dBc</b>	<150	
Impedance	50 ohm	
Radiation/Polarization	Omni-Directional/ Horizontal	
Material	ABS Radome	
Colour	White	
Weight <b>Grams</b>	420	
Max. Power <b>Watts</b>	50	
Connector	N Female	
Cable	RG402 Pigtail	
Mounting Method	Ceiling Mount, stud/nut with thru-cable	
Dimensions <b>mm</b>	200 dia. x 120(h)	
Temperature Rating <b>degrees C</b>	-40 to +55	

Email: [sales@comnet.com.au](mailto:sales@comnet.com.au)  
 Website: [www.comnet.com.au](http://www.comnet.com.au)  
 Telephone: +61 2 9899 5700

Comnet Solutions  
 19/9 Hoyle Avenue  
 Castle Hill NSW 2154  
 Australia