

9dBi Heavy Duty Bull Bar Antenna 3G/4G/5G NG9OMNI-6A-F

This rugged outdoor Omni antenna has a black fibreglass radiator and black heavy duty stainless steel spring. Designed for use on vehicles, the wideband frequency range of 690 to 2700MHz provides versatility for connections to 3G, 4G, 5G NR services across Australia. Comes with a 5 meter LMR195 grade cable terminated with FME Female connector.

Recommendations/Installation

Ideal for mounting on vehicle bull bars or bonnet/boot using optional stainless steel mounting brackets. Good for flat terrain with poor to marginal service areas 1 bar. Wrench used to fasten bottom nut, screwdriver and other tools may also be needed depending on mounting option. Cable must be run from the antenna to interior of the vehicle. Skills required.

| Specifications: | | | |
|------------------------------|---|-----------|-----------|
| Freq. Range MHz | 690-960 | 1710-2170 | 2300-2700 |
| Gain dBi | 9 | 4 | 3 |
| VSWR | <1.6:1 | | |
| Impedance | 50 ohm | | |
| Polarization | Vertical | | |
| Radiation | OMNI | | |
| Material | Fibreglass Radiator, Stainless Steel Spring | | |
| Colour | Black | | |
| Weight Grams | 850 | | |
| Max. Power Watts | 100 | | |
| Connector | FME Female | | |
| Cable | 5m Low Loss LMR195 grade | | |
| Mounting Method | Nut fastened 15.7mm diameter Threaded Stud | | |
| Dimensions mm | 1150(h) | | |
| Temperature Rating degrees C | -40 to +60 | | |

Email: sales@comnet.com.au
Website: www.comnet.com.au
Telephone: +61 2 9899 5700

Comnet Solutions 19/9 Hoyle Avenue Castle Hill NSW 2154 Australia